

FS Star

Sigle fired floor tiles







FS STAR Blue




FS STAR Oxide



FS STAR Sage



FS STAR N



9 patterns

45 * 45 * 1,05 cm | 17 3/4 * 17 3/4 * 7/16"

NO RECTIFIED	NATURAL PRICE CODE BN14
BLUE	23200
OXIDE	23198
SAGE	23199
N	19136

CARACTERÍSTICAS TÉCNICAS ANTIDESLIZAMIENTO ANTI-SLIP CHARACTERISTICS		
Ensayo Essay	Características Features	Resultado Result
DIN 51130	Ángulo crítico (Pies calzados) Critical angle (footwear)	R9
DIN 51097	Ángulo crítico (Pies descalzos) Critical angle (Wet loaded barefoot)	—
BS-7976-2	Antideslizamiento (Test del péndulo) Slip resistance (Pendulum test)	+36 Wet
UNE-ENV-12633	Antideslizamiento (Test del péndulo) Slip resistance (Pendulum test)	Class 1
ANSI A.1371:2012	Coefficiente de Fricción Dinámico Dynamic Coefficient of Friction	>0,42
ISO 10545-7	Resistencia a la Abrasión Superficial/Resistance to Surface Abrasion	PEI 4

APLICACIONES APPLICATIONS		
Área Area	Revestimiento Wall	Pavimento Floor
Interior Internal	✓	✓
Exterior External	-	-
Comercial Commercial	✓	-
Ducha Shower	✓	-

CARACTERÍSTICAS TÉCNICAS TECHNICAL CHARACTERISTICS		
joint 1,5 mm 	versatile 	matt
diferent shades 	shade variation V2 	various graphics

Formato Sizes		Cajas Boxes			Pallet			Cont./20' 21500 kg.	Cont./20' 24000 kg.	
cm		Piezas	m ² / sq.m	kg	Cajas	m ² / sq.m	kg	Tamaño cm aprox.	m ² / sq.m	m ² / sq.m
45 * 45 * 1,05		5	1,00	23,14	66	66,00	1552,24	102 * 80 * 105	914,16	1020,46
inch		Units	ft ²	lb	Boxes	ft ²	lb	Sizes inch approx.	ft ²	ft ²
17 3/4 * 17 3/4 * 7/16		5	10,76	50,91	66	710,42	3414,93	40 3/16 * 31 1/2 * 41 5/16	9839,96	10984,14